

KS EVO

ROBUST, SILENT AND EFFICIENT

PRO LINE

YEARS OF WARRANTY | 3



- ➔ Easy maintenance: rapid access to the prefilter (no tools required)
- ➔ Impeller and diffuser made of Noryl®, very hard-wearing and corrosion-resistant
- ➔ Evolution of the KS: silent and efficient operation
- ➔ Simple installation, direct substitute for KSE pumps, supplied with 50/63 mm unions
- ➔ Double drain, easy opening (no tools required)
- ➔ Suitable for use in salt water. AISI316 Mechanical seal
- ➔ **Usage: for residential pools up to 198 m³**

	Code	Ref.	P2 Hp	P1 kW	A (mm)	Flow rate (m ³ /h)*	Weight (kg)	Pack. (mm)	qty/pallet	M.O.Q**
SINGLE PHASE	012501225010	KS Evo 033M	0,33	0,45	543	4,8	11,2	330 x 255 x 650	25	1
	012511320510	KS Evo 050M	0,50	0,58	590	7,5	12,5	330 x 255 x 650	25	1
	012511420510	KS Evo 075M	0,75	0,75	590	11,5	13,5	330 x 255 x 650	25	1
	012511520510	KS Evo 100M	1,00	1	590	15,4	14	330 x 255 x 650	25	1
	012521120520	KS Evo 150M	1,50	1,6	620	21,9	16,5	330 x 255 x 650	25	1
	012521220520	KS Evo 200M	2,00	1,92	620	25,7	22,5	330 x 255 x 650	25	1
	012521420520	KS Evo 300 M	3,00	2,60	620	33	25	330 x 255 x 650	25	1
THREE PHASE	012511350510	KS Evo 050T1	0,50	0,58	590	7,5	12,5	330 x 255 x 650	25	1
	012511450510	KS Evo 075T1	0,75	0,75	590	11,5	13,5	330 x 255 x 650	25	1
	012571050510	KS Evo 100T1 IE3	1,00	1	620	15,4	16,5	330 x 255 x 650	25	1
	012571150510	KS Evo 150T1 IE3	1,50	1,6	620	21,9	19	330 x 255 x 650	25	1
	012581250510	KS Evo 200T1 IE3	2,00	1,92	620	25,7	25	330 x 255 x 650	25	1
	012581350520	KS Evo 300 T1 IE3	3,00	2,60	620	33	27	330 x 255 x 650	25	1

P1: Input Power

P2: Nominal Power

* 10 m water column pressure

** (minimum order quantity)

60 Hz on request, ask for conditions; ANSI or JIS on request

IE3 ✓

IE3 ✓

IE3 ✓


IE3 ✓

NEW

LPRK Smart retrofit kit: use it with the KS EVO to replace easily old pumps on existing installations

SMART RETROFIT KIT

Item	Pumps to replace	Kit content	Kit per box
LPRK	Astral Victoria Plus, Astral Victoria Plus Silent, Saci Winner	Smart Base (1), Fixing screw (3), RC50 (2), O-ring Seal (2)	10



LPRK is valid to retrofit installations Ø50 mm, commonly used for pumps up to 1 HP

Technical Specifications

Max. water temp. / Max. pressure	50°C/ 2,5 bar
Connection (DIN slip included, for others please ask)	Ø 50 mm (0,33 - 1 HP) / Ø 63 mm (1,5 - 3 HP)
Mechanical seal	AISI 316, suitable for sea water
Motor-drive specifications	Class F, IP55, 50 Hz, 2850 rpm
Housing/impeller/strainer/lid	PP + F.G./Noryl®/PP/SAN®

Water column pressure (m) KS Evo / KSX Pro Q (m³/h)-H (m)

