

AquaRite® Flo Advanced

EXPERT LINE

YEARS OF WARRANTY


3 STANDARD
4 YEARS
8000 HOURS

Cell



As defined by EN 17645.
Go to report pages to see
the complete detail by item.

MORE THAN A SALT CHLORINATOR!

- **Salt chlorinator** combined with the control of pool equipments
- Wide range of Chlorine production, 8, 16, 22, 33, 50 gr/h and 2 items LS **covering the needs of all pools on the market**
- **Transparent cell** to enable a visual check of the production
- **Monitoring** of the filtration pump and the lighting
- No need of an additional transformer for the lighting, **the power is provided directly by the control unit for LED lights up to 50W**
- **pH, ORP kits** and temperature sensor available as an option
- Wifi and Ethernet optional connection kits available for a **remote control of the pool equipments**



INCLUDED



Cl₂ Production

DISPLAY
GRAPHIC


Up to 50 W


Salt water
& Sea water
compatible

Control of filtration
and VS pumps

Modbus
protocol

Free Hayward®
Poolwatch app

AQUARITE®
FLO
ADVANCED

AVAILABLE
OPTIONS

Description	AQR-FLO-AD8	AQR-FLO-AD16	AQR-FLO-AD22	AQR-FLO-AD33	AQR-FLO-AD50	AQR-FLO-AD16LS	AQR-FLO-AD33LS
Maximum production Cl ₂ /h	8 g/h	16 g/h	22 g/h	33 g/h	50 g/h	Equiv. 15 g/h	Equiv. 30 g/h
Average pool volume	30 m³	75 m³	100 m³	150 m³	200 m³	60 m³	120 m³
Salt concentration	3 to 100 g/l					1.5 to 100 g/l	
Display	Graphics display shows present production, cover, pH*, mV*, temp*						
Protection	IP65						
Superchlorination mode	●	●	●	●	●	●	●
Manual adjustment of Cl	●	●	●	●	●	●	●
Lighting management (supply up to 50W)	●	●	●	●	●	●	●
Filter pump / VSTD pumps management	●	●	●	●	●	●	●
Cover detection	●	●	●	●	●	●	●
Smart mode: adjustment of Cl	●	●	●	●	●	●	●
Mechanical Flow Switch	●	●	●	●	●	●	●
Gas detector	●	●	●	●	No	●	●
Self-cleaning	Programmable up to 999 min						
Alarms	Low salt / no flow / pH (60 minutes) / AL4 for cell configurable						
Control box dimensions	254 x 298 x 133						
pH kit	BKPER-OPTION-PH (plastic premium probe) / BGKPER (glass probe) - (1.5 L/h peristaltic pump)						
Redox kit	E-OPTION-REDOX (plastic premium probe) / EG (glass probe)						
Temperature kit	T-OPTION-TEMP (give access to smart filtration mode)						
WiFi module	RS4WI-OPTION-W						
Ethernet module	RS4NET-OPTION-L						
Pool Terre	KV02						



Flow switch included



pH kit as standard


Redox probe kit as
standard


Temperature kit



WiFi module



Ethernet module

Complete your installation

Supply your filtration pump
and salt chlorinator with
HPOWERPRO-A

